

BARCODE TICKET READER*by Inventor*

Stephen P. Shoemaker, Jr.

5

CROSS REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of U.S. Provisional Patent Application number 60/255,637 filed on December 12, 2000 and is incorporated herein by reference.

FIELD OF THE INVENTION

The present invention relates generally to ticket counting in the amusement industry and more particularly to automatic ticket counting mechanisms.

BACKGROUND OF THE INVENTION

Tickets are a convenient way for proprietors to grant consumers access to goods and services. Typical examples include admission to shows and prize redemption. When tickets are redeemed, it is desirable to accurately count the tickets and keep a running total.

Figure 1 shows an example set of tickets **10**. Each ticket can be separated at perforations **12**. At each perforation **12**, there is a notch **14** on both ends of a ticket. The notch **14** is commonly used to count tickets, as will be explained subsequently. Figure 2 shows a top view of tickets **10** being fed into a counter device **16**. Figure 3 shows a side view of tickets **10** being fed into the same counter device **16**. Tickets **10** are fed into the counter device **16** as indicated by directional arrow **18**.

145 01280" 55055E 060

Rollers 20 pull the tickets 10 into the counter device 16. As the tickets 10 are pulled in, the edge of the ticket with the notch 14 (not shown) passes over the illuminator 22 and lens 24. The illuminator 22 sends out illumination which is focused by the lens 24. As the notch 14 reaches the illuminator 22 and the lens 24, illumination passes through notch 14 and is substantially blocked elsewhere by the ticket material. This produces a characteristic analog signal which is detected by a detector 26, and is sent through processing electronics 28. Processing electronics 28 converts the analog signal into a digital signal 30.

10 The signal strength is dependent on where the focused illumination passes over the notch 14. Figure 4 shows how the signal strength varies depending on where the focused illumination is read on the notch. Ticket signal 32 was produced from a focused illumination being read at location 34 in notch 36 on ticket 38. For ease of illustration, the ticket 38 and associated notch 36 are shown as a top view. The focused illumination passes through the notch perpendicular to this view, however. Since ticket signal 32 was read at location 34, a high signal strength is observed, above the minimum signal strength needed for detection. Conversely, ticket 40 with associated notch 42 is read at location 44. Location 44 represents a smaller cross-sectional area as compared to location 34. As a result, ticket signal 46 is much lower in magnitude than comparable ticket signal 32. Also, ticket signal 20 46 is at about the minimum signal strength needed for detection and successful counting of ticket 40 is doubtful. This situation can result when the notch is not evenly divided between the two tickets resulting in a smaller than normal notch and a degraded signal strength. Additional drawbacks to this method include the fact that the ticket must be opaque so that the light does not pass through the ticket. 25 Due to this requirement, dust or contamination can possibly interfere with the

operation since they can block light. Also, the notch can be a point of jamming in ticket counting mechanisms since the cutout portion can possibly catch.

Another method of counting tickets involves printing a barcode on the ticket and using one of the widely available barcode scanners to count the ticket. This method, while arguably an improvement over using notches, still has drawbacks. Since a barcode scanner works on reflective principles, a ticket needs to be oriented correctly when inserted into a ticket counting mechanism. Otherwise the scanner will not see the barcode. This can be avoided by printing the barcode on both sides, but that in turn increases the cost of printing and also limits the space that is otherwise available to print information such as advertisements.

Additionally, two barcode scanners can be included in the mechanism if both sides of a ticket has a barcode. While this does resolve the orientation issue when loading a ticket into the ticket counter, it significantly adds to the cost of the ticket counter.

Accordingly, what is needed is a tool to accurately count tickets that is not dependent upon variations in ticket notch size or subject to the constraints of typical reflective barcode scanning techniques.

SUMMARY OF THE INVENTION

The present invention provides an apparatus and a method for counting tickets having a printed pattern.

5 A method to count tickets in accordance with the present invention includes providing a translucent ticket with an opaque pattern with translucent portions, providing a light source on a first side of the ticket, providing a detector on a second side of the ticket and providing relative motion between the ticket and the detector. The pattern and translucent portions are detected with the detector.

An apparatus for counting tickets in accordance with the present invention includes a housing and a transport device coupled to the housing capable of guiding at least one ticket into the housing and the tickets are printed with a pattern. A light source is positioned on a first side of the ticket and a detector positioned on a second side of the ticket. A signal analyzer coupled to the detector is used to analyze the signal provided by the detector.

10 A method for printing a pattern on a ticket in accordance with the present invention includes obtaining a plurality of translucent tickets, feeding the plurality of translucent tickets into a ticket printing machine, printing an opaque pattern on one side of each individual translucent ticket and covering the opaque pattern with a dark colored non-opaque ink.

20 An advantage of the present invention is that the pattern only needs to be printed on one side and can be detected independently of the orientation to a detection apparatus. The apparatus and method are suited to quickly and inexpensively count tickets.

FOI(b)7 - DSSS 00101

Another advantage of the present invention is that it eliminates the need for a notch on both ends of a ticket, reducing the chance that a ticket may get stuck in a ticket counting machine. Another advantage of the present invention is that the pattern does not need to be printed on both sides of a ticket, which reduces printing costs.

5

These and other advantages of the present invention will become apparent to those skilled in the art after reading the following descriptions and studying the various figures of the drawings.

FOR "55092660"

DETAILED DESCRIPTION OF THE INVENTION

5 Figs. 1-4 were described with reference to the prior art. Figure 5 is an exemplary embodiment of the present invention of a series of tickets. A set of tickets **48** includes individual tickets **50**, **52** and **54**. Tickets **50**, **52** and **54** can be separated, for example, at perforations **56** and **58**. On each of tickets **50**, **52** and **54** there is a pattern **60** defining translucent portions **61**. As used herein, "translucent" means that electromagnetic radiation (e.g. visible light) can be transmitted through a ticket at the translucent portions to a greater extent than at the pattern **60**. The pattern **60** typically are dark/black regions made up of an opaque ink film which greatly reduce the transmission of light through the tickets. The translucent regions permit light to go through the paper ticket to a greater extent than through the ink film pattern. It should be understood that the terms "pattern" and "barcode" can be used interchangeably in the context of the present invention. "Translucent" can range from transparent to relatively opaque as long as the amount of light transmitted through the ticket at the translucent portions is distinguishable from that of the pattern. "Opaque" signifies that significantly less light passes through as compared to "translucent".

10
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995

Figure 6A illustrates how tickets are read employing the present invention. Formed on ticket **62** is pattern **64**, typically made from a dried ink film. Upon illumination of ticket **62** with a light source (an LED for example), a characteristic signal can be detected on the other side of the ticket by a photodetector. This signal is shown on graph **66** and shows the signal strength versus lateral distance on the ticket. As can be seen, a characteristic pattern results corresponding to the translucent/patterned regions of the ticket. The opaque regions correspond to areas of low signal strength and the translucent regions correspond to the areas of high signal strength.

Similarly, Figure 6B shows a ticket **62a** and a pattern **64a**, typically made from a dried ink film. Graph **66a** shows the signal strength versus lateral distance when a light source illuminates the ticket **62a**, in combination with a photodetector, at the location of the pattern **64a** indicated by the directional arrow, at the side edge of the ticket (square opaque area). There will be no variation of signal strength relative to the positioning of the photodetector/illumination along this section of the pattern **64a**.

It will therefore be appreciated that a method to count tickets includes providing a translucent ticket with an opaque pattern with translucent portions, providing a light source on a first side of the ticket, providing a detector on a second side of the ticket and providing relative motion between the ticket and the detector. The pattern and translucent portions are detected with the detector. Additionally, a running total of the number of tickets, verified tickets and non-verified tickets can be incremented.

Figure 7 is a block diagram of a ticket counter **68** in a preferred embodiment of the present invention. Housing **69** contains ticket counter **68**. Tickets **70**, which have a pattern/barcode, are inserted into the ticket counter **68**. A ticket sensor **72** sees the ticket **70** and indicates a signal to the controller **74**. The controller **74** turns on the ticket transport **76** and moves the ticket **70** in the direction of the ticket chopper **90**, which runs concurrently with the ticket transport **76**. As the ticket **70** is conveyed by the ticket transport **76**, the ticket **70** passes between the barcode backlight **78** and the barcode detector **80**. Also included is a focusing slit **79** that is used to focus the illumination coming from barcode backlight **78**. An enlarged/top view of the focusing slit **79** is shown at **79a**. Upon sensing the presence of a barcode on the ticket **70**, the barcode detector **80** sends a signal, containing the barcode information, to the controller **74**. The program instructions **82**, in the

controller 74, will determine if the barcode pattern matches the pattern for a legitimate ticket. The program instructions 82 counts the number of valid and invalid ticket counts in the data memory 84. In addition, the controller 74 might send signals to the sound output 86 to generate music to indicate the counting of tickets to a customer (not shown) and display a running total of the tickets 70 counted via ticket count display 88. When the ticket 70 reaches the ticket chopper 90, it is destroyed into shredded tickets 92, so that the ticket 70 cannot be used again. When there are no more tickets 70 to be counted, the ticket sensor 72 sends a signal indicating the absence of tickets to the controller 74. After a short time delay (to convey all of the tickets 70 to the shredded tickets 92), the controller 74 shuts off the ticket transport 76. After all the tickets 70 have been counted, a customer may request a receipt by depressing print receipt button 92 that activates receipt printer 94. Receipt 96 is then printed by receipt printer 94.

It will therefore also be appreciated that an apparatus for counting tickets includes a housing and a transport device coupled to the housing capable of guiding at least one ticket into the housing and the tickets are printed with a pattern. A light source is positioned on a first side of the ticket and a detector positioned on a second side of the ticket. A signal analyzer coupled to the detector is used to analyze the signal provided by the detector. The signal analyzer can be a controller that counts, analyzes and determines barcode similarity relative to a location code. The location code is a pattern stored in the controller memory that it uses to determine if the pattern on a ticket is valid or not. The controller can also contain a digital processor or CPU, a data memory and a program instruction.

The apparatus can also include a ticket chopper, a ticket count display and a receipt printer. The ticket chopper is more fully described in U.S. Provisional Patent Application number 60/255,637, incorporated herein by reference.

Figure 8 is an exemplary printing process **98** for printing a pattern on a set of tickets. The printing process **98** begins at operation **100** where a plurality of tickets are first obtained. The tickets are then loaded into a ticket printing machine in operation **102**. In operation **104**, a pattern is printed on one side of each ticket.

5 Printing process **98** then terminates at operation **106**.

Printing process **98** can also optionally include operation **104a** where the pattern is printed on the other side of the ticket. Printing the pattern on both sides of the ticket is usually only necessary when the ticket paper is of a very dark color which necessitates the use of a brighter light to see through the paper.

Operation **104b** can optionally also be performed. This involves covering one or both patterns with a dark colored non-opaque ink. Operation **104b** advantageously prevents individuals from making counterfeit tickets via the use of a copier machine. If a legitimate ticket is copied that has a pattern covered by a dark colored non-opaque ink, the counterfeiter will only see a dark block on the copy that is useless in the ticket counter embodiment of the present invention. The copied ticket does not have the pattern and will not be counted by the ticket counter.

Another advantage of this embodiment is that a conventional reflective optical reader can not read the pattern covered by the dark colored non-opaque ink.

20 One skilled in the art will readily recognize that operations **104**, **104a** and **104b** can all be done interchangeably. One skilled in the art will also readily recognize that the pattern can be printed on one side of the ticket and both sides can be covered by the non-opaque ink.

In view of the foregoing, it will be appreciated that a method for printing a pattern on a ticket includes obtaining a plurality of translucent tickets, feeding the plurality of translucent tickets into a ticket printing machine, printing an opaque pattern on one side of each individual translucent ticket and covering the opaque pattern with a dark colored non-opaque ink. Optionally, the pattern and dark colored non-opaque ink can be printed on both sides of the ticket. Also, the pattern can be printed on one side of the ticket and the non-opaque ink can be printed on both sides.

Preferred ticket stock includes computer type printer paper. Example opaque and non-opaque inks can be obtained from the Environmental Inks and Coatings Corp. of Holland, under the brand names of Environmental Inks.

While this invention has been described in terms certain preferred embodiments, it will be appreciated by those skilled in the art that certain modifications, permutations and equivalents thereof are within the inventive scope of the present invention. It is therefore intended that the following appended claims include all such modifications, permutations and equivalents as fall within the true spirit and scope of the present invention.

What is claimed is: